


# Specifications



MODELS	IWP™-20S		IWP™-25S		IWP™-30S	
MEASUREMENTS	Metric	US	Metric	US	Metric	US
Working height*	8.24 m	26 ft 6 in	9.44 m	30 ft 5 in	11 m	35 ft 6 in
Platform height	6.24 m	20 ft 6 in	7.44 m	24 ft 5 in	9 m	29 ft 6 in
<b>A</b> Horizontal outreach**	66 cm	2 ft 2 in	—	—	—	—
<b>B</b> Height - stowed:						
fully lowered	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in
base raised	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
<b>C</b> Length	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
<b>D</b> Width - standard base	81 cm	2 ft 8 in	81 cm	2 ft 8 in	—	—
wide base	—	—	—	—	1.02 m	3 ft 4 in
Corner access***	15 cm	6 in	15 cm	6 in	18 cm	7 in
<b>PRODUCTIVITY</b>						
Lift capacity	159 kg	350 lbs	159 kg	350 lbs	159 kg	350 lbs
Platform Dimensions (l/w/h)						
Standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated narrow	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in
Standard fibreglass**	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in
<b>POWER</b>						
AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz					
DC models	12V / 110 V / 60 Hz or 110/230 Hz worldwide model					
<b>SOUND &amp; VIBRATION LEVELS</b>						
Sound pressure level (ground workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Sound pressure level (platform workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Vibration	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>
<b>WEIGHT****</b>						
<b>Standard base</b>						
AC	565 kg	1,245 lbs	585 kg	1,290 lbs	—	—
DC	610 kg	1,345 lbs	630 kg	1,390 lbs	—	—
<b>Standard base with outreach option</b>						
AC	612 kg	1,350 lbs	—	—	—	—
DC	658 kg	1,450 lbs	—	—	—	—
<b>Wide base</b>						
AC	—	—	—	—	649 kg	1,430 lbs
DC	—	—	—	—	694 kg	1,530 lbs
<b>Wide base with outreach option</b>						
AC	658 kg	1,450 lbs	—	—	—	—
DC	703 kg	1,550 lbs	—	—	—	—

**STANDARDS COMPLIANCE**

CE EN280, PB-10-611-03

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.  
 \*\* Gated ultra narrow, front and side entry extra-large, and fibreglass platforms are not available with the outreach option.  
 \*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.  
 \*\*\*\* Weight will vary depending on options and/or country standards.

## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated narrow platform
- Standard fibreglass platform

#### POWER OPTIONS

- AC power 110 V / 50-60 Hz
- AC power 220 V / 50-60 Hz
- DC power 110 V / 50-60 Hz
- DC power 110/230 V / 50-60 Hz worldwide model
- Power assist option

#### BASE OPTIONS

- Standard base (IWP™-20S and 25S only)
- Wide base (IWP™-30S only)

### STANDARD FEATURES

#### MEASUREMENTS

##### IWP™-20S

- 8.24 m (26 ft 6 in) working height
- 6.24 m (20 ft 6 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Outreach option adds 61 cm (2 ft) of horizontal reach
- Up to 159 kg (350 lb) lift capacity

##### IWP™-25S

- 9.44 m (30 ft 5 in) working height
- 7.44 m (24 ft 5 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Up to 159 kg (350 lb) lift capacity

##### IWP™-30S

- 11 m (35 ft 6 in) working height
- 9 m (29 ft 6 in) platform height
- 1.02 m (3 ft 4 in) wide base width
- Up to 159 kg (350 lb) lift capacity

#### PRODUCTIVITY

- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Choose from standard or wide base
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt power receptacle
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

#### POWER

- AC power 110 V / 50-60 Hz (not CE)
- AC power 220 V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system



### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Gated standard platform
- Gated narrow platform
- Standard fibreglass platform (not available with outreach)
- Outreach option (IWP™-20S only)
- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

#### POWER

- Power wheel assist with dual battery package\*
- Dual battery package

\* Adds 32 cm (12.5 in) to unit length and 129 kg (285 lbs) to unit weight

#### Enquiries from Europe:

Tel: +31 165 519 361  
Fax: +31 165 511 148  
Email: AWP-InfoEurope@terex.com

#### Offices:

##### France

Tel: +33 (0)2 37 26 09 99  
Fax: +33 (0)2 37 26 09 98

##### Germany

Tel: +49 (0)4221 491 810  
Fax: +49 (0)4221 491 820

##### Spain

Tel: +34 93 572 50 90  
Fax: +34 93 572 50 91

##### Scandinavia

Tel: +46 31 57 51 00  
Fax: +46 31 57 51 04

##### The Netherlands

Tel: +31 165 519 361  
Fax: +31 165 511 148

##### UK

The Maltings  
Wharf Road  
Grantham NG31 6BH  
UK  
Tel: +44 (0)1476 584333  
Fax: +44 (0)1476 584334

##### Middle East

Tel: +971 4 399 0381  
Fax: +971 4 399 0382  
Email: AWP.Infome@terex.com

##### Russia & CIS countries

Tel: +7 495 660 32 30  
Fax: +7 495 660 32 29  
Email: info@terexrus.ru

#### Corporate Headquarters:

##### Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, WA  
USA 98073-9730  
Tel: +1 425 881-1800  
Fax: +1 425 883-3475

#### Distributed By: