

Model **260MRT**

ROUGH TERRAIN MINI SCISSOR LIFT

Specifications





Dimensions

A. Platform Height Elevated 26 ft (7.92 m) B. Platform Height Lowered 4 ft 1.5 in. (1.26 m) C. Platform Railing Height 3 ft 7.5 in. (1.1 m) D. Overall Height 7 ft 9.5 in. (2.37 m) E. Platform Size 65 x 102 in. (1.65 x 2.59 m) F. Platform Extension 4 ft (1.22 m) G. Overall Width 5 ft 9 in. (1.75 m) H. Overall Length (no outriggers) 8 ft 9 in. (2.67 m) 6 ft 6 in. (1.98 m) I. Wheelbase J. Ground Clearance 8 in. (20 cm) Platform Capacity 1,250 lb (567 kg) Capacity on Deck Extension 300 lb (136 kg) Lift/Lower Speed 27/21 sec. Maximum Drive Height Full Height 7,360 lb (3,338 kg) Gross Vehicle Weight

Chassis

Drive Speed-Lowered 3.5 mph (5.6 kmph) 0.4 mph (0.6 kmph) Drive Speed-Elevated Gradeability 35% Turning Radius (inside) 84 in. (2.13 m) Tire Size/Type 26 x 12 Lug Tread Spring Applied Hydraulically Released **Brakes**

Power system Dual Fuel Engine Kubota 24.5 hp (18.3 kW) Kubota 22.5 hp (16.8 kW) 7.5 gal. (28.39 L) Diesel Engine Fuel Tank Capacity Hydraulic Reservoir 15 gal. (56.78 L)



Standard Cross Corner Four-Wheel Drive for Terrainability



Strengthened Arm Stack for Improved Stack Rigidity

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs our products with our exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) full years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453 and ANSI A92.6-2006 as originally manufactured for intended applications.

Distributed By:



1 JLG Drive

McConnellsburg, PA 17233-9533 Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT Fax 717-485-6417 www.jlg.com

JLG Industries, Inc.

An Oshkosh Corporation Company

www.onesourcerental.com

Form No.: SS-260MRT-100-60M Part No.: 3131404 R100808 Printed in USA