

M26-2 M26-4

	M26-2 / M26-2H	M26-4
Lifting		
Max. capacity	2 600 kg at 500 mm CDG	
Lifting height (standard mast)	3.70 m	
Max. lifting height	7.00 m	
Unladen time		
Lifting	0.5 m/s	
Lowering	0.5 m/s	
Tyres		
Forward	14,5R20 18PR MPT80 TL	400/70-20 150B T37 STAB TL
Backward	10R17,5 134/132M G291	10,5/80-18 10PR TG42 TL
Braking		
Service brake	Oil immersed multi-disc braking on front/rear axles	
Parking brake	Oil immersed multi-disc mechanics on the front axle	
Engine		
Type	PERKINS - STAGE EURO 3B	
Cubic capacity	PERKINS 854F-E34T 54009,1,1 3 400 cm ³	
Power	75 cv / 55.5 kW	
Max.torque	318 Nm at 1 400 tr/min	
Injection	Direct	
Cooling	Water	
Laden drawbar pull	4 670 daN	6 290 daN
Transmission		
	Torque converter	Hydrostatic
Gearbox	Mechanical	Mechanical
Reversing shift	Electro-hydraulic	Electro-magnetic
Number of gears (forward/reverse)	4 / 4	4 / 4
Max. travel speed	22.1 km/h	21.6 km/h
(may vary according to applicable regulations)		
Front axle differential lock	yes	no
Control for 2/4 wheel drive	no	yes
Controls		
	Hydro-proportional levers for all movements	
Hydraulics		
Pump	Gear pump 97 l/min - 245 bar	
Capacities		
Hydraulic oil	80 l	
Fuel	85 l	
Unladen weight (with standard mast forks)	5 089 kg	5 284 kg
Dimensions		
1. Front wheel centre to carriage	0.75 m	
2. Wheelbase	1.99 m	
3. Rear wheel centre to rear face	0.76 m	
4. Overall length to carriage	3.49 m	
5. Ground clearance	0.38 m	0.39
6. Inside tyre width	1.55 m	1.52 m
7. Overall width	1.90 m	1.92 m
8. Overall height	2.73 m	
Standard forks (length x width x thickness)	1 200 x 125 x 40 mm	
Turning radius	3.49 m	4.27 m
Tilt standard mast (forward/backward)	6° / 12°	
Noise and vibration		
Noise at driving position (LpA)	76 dB	
Environmental noise (LwA)	104 dB	
Vibration to whole hand/arm	< 2.5 m/s ²	
Vibration on driver's body	0.97 m/s ²	

